

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/076735 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/IL2005/000179

(22) International Filing Date: 11 February 2005 (11.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/544,438 12 February 2004 (12.02.2004) US
60/642,233 6 January 2005 (06.01.2005) US

(71) Applicant (for all designated States except US): MICRO-HEAT INC. [US/US]; 27611 Halsted Road, Farmington Hills, MI 48331-3511 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ARKASHEVSKI,

Uri [IL/IL]; 36 Vaad Arba Arazot Street, 49300 Petach Tikva (IL). ROGOZINSKI, Joseph [IL/IL]; 14 Motza Street, 52366 Ramat Gan (IL).


(74) Agents: SANFORD T. COLB & CO. et al.; P.O. Box 2273, 76122 Rehovot (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR CLEANING AND DE-ICING



(57) Abstract: A windshield heated liquid spray assembly including a liquid heating assembly and a heated liquid spray assembly operative to spray the heated liquid onto a windshield, the liquid heating assembly including a liquid heating chamber, at least one heating element disposed in the liquid heating chamber and at least one heat dissipator in heat conduction contact with the at least one heating element, the at least one heat dissipator at least partially defining at least one liquid flow channel and being operative to transfer heat from the at least one heating element to the liquid flowing through the at least one liquid flow channel.

WO 2005/076735 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*